



## FTB102SA Max 2 Ports Fiber Wall Socket

Fibre Wall Socket / Premises Terminal Box (CPE Site)

SIRIM Tested UL94V-0 Flame Retardant (report number: 2014PC0561)

Slim and compact design 86mm x 86mm x 18mm



### Application

Used in the end termination of residential buildings, office and villas, to fix and terminated with SC FTTH quick termination connector

### Features

- Compact, small size, light weight, pleasing in appearance
- Can be installed on the wall with mechanical protective function
- May adapt variety of optical connection styles.
- Optical fiber can be managed effectively
- Set strengthen device and fiber optic cable mounting seat
- SC 2 ports, Max capacity for SC 2 ports (Simplex)
- Suitable for indoor wall mount.

### Specification

|                           |  |
|---------------------------|--|
| Item                      | FTB-102SA                                      |
| Dimension (mm)            | H86mm×W86mmx D18mm                             |
| Weight (kg)               | 0.055  |
| Cable diameter (mm)       | Φ7~Φ14   |
| Cable ports               | 2 holes  |
| Material                  | PC with UL94V-0 Rated Flame Retardant Material |
| Number of the splice Tray | N/A  |
| Max capacity of cable     | 2 (single fiber)                               |

### Standard Accessories

SC/UPC Simplex Adapter with shutter and Part Number: N3004AS 1 no with Laser warning sign (blue casing)

### Order Information

Product Name: NETWAY FIBER WALL SOCKET (86x86x18mm) Part Number: FTB102SA